

MADE IN FRANCE
MANUFACTURER SINCE 1964



NOUVEAUTÉS • NEW • NEUHEITEN



INVEST IN THE FUTURE



Chargers, Boosters & Starters

Catalogue Chargeurs • Batterieservicegeräte-Katalog • Catálogo de Cargadores

2014

www.gys.fr

CHARGERS • BOOSTERS • STARTERS • TESTERS • JUMPER CABLES • ACCESSORIES

Distributed In 104 Countries
Distribué Dans 104 Pays
Export in 104 Länder

www.gys.fr



GYS France - HEADQUARTER
Laval



GYS U.K.
Warwick



GYS Germany
Aachen




GYS China
Shanghai



GYS India
Coimbatore

INDUSTRIAL GROUP SINCE 1964

Société familiale
Family firm
Familienbetrieb



100 % Production intégrée
In-house Manufacturing
integrierter Produktion



Centre de R&D R&D Center F&E Zentrum
Mécanique Mechanics Mechanik
Tôlerie / Filerie Metal work / Cable work Blechfabrik / Verdrahtung
Transformateurs Transformers Transformator
Electronique Electronics Elektronik
Montage Assembly Montage
Logistique Logistics Logistik



Your Charger Partner
Votre Partenaire Chargeur
Produktvielfalt, die Überzeugt

Chargers



Boosters & Starters




Jumper cables, Testers & Accessories



Awards



Homologations



Certifications



CHARGERS
TRADITIONAL

W
p. 35

3 A 12V
ENERGY 124



Ref. 023215
Ref. 025141

4 A 12V
ENERGY 126



Ref. 023222
Ref. 025165



CHARGERS
AUTOMATIC

WU
p. 35

PATENTS REGISTERED NUMBERS
001652090-0001
EUROPEAN TRADEMARK & DESIGN

TCB 60/90/120

2/4 A 12V
TCB 60



Ref. 023253
Ref. 025189

2/5,5 A 12V
TCB 90



Ref. 023260
Ref. 025202

3,5/7 A 12V
TCB 120



Ref. 023284
Ref. 025240



CHARGER
AUTOMATIC
& STARTER

W2
p. 35

PATENTS REGISTERED NUMBERS
001652090-0002
EUROPEAN TRADEMARK & DESIGN

START UP 80

9/17 A 12V
START UP 80



Ref. 024922 Ref. 025127

3 in 1

=
CHARGE
+
TEST
+
START



Fuse X10

10A : Ref.054530
15A : Ref.054493

						CHARGE 			START 				 Recommendation						CHARGER + TESTER	BOOST	 Bzz CONTROL
			50 / 60 Hz				Efficace / RMS	Moyen / Average (EN 60335)	1V/C	Fuse					Essence • Petrol • Benzin			Diesel			
ENERGY 124	023215	 025141	230V	70W	12V	—	4,5 A	3 A	—	10 A	11,5 x 16 x 22 cm	2,2 kg	ENERGY 124						—	—	—
ENERGY 126	023222	 025165	230V	90W	12V	—	6 A	4 A	—	10 A	11,5 x 16 x 22 cm	2,2 kg	ENERGY 126			10 > 45 Ah 15 > 60 Ah			—	—	—
TCB 60 automatic	023253	 025189	230V	85W	12V	2	6 A	2 - 4 A	—	10 A	12 x 17 x 29 cm	2,7 kg	TCB 60 automatic		15 > 60 Ah				OK	—	OK
TCB 90 automatic	023260	 025202	230V	120W	12V	2	8 A	2 - 5,5 A	—	15 A	12 x 17 x 29 cm	3,4 kg	TCB 90 automatic		15 > 90 Ah				OK	—	OK
TCB 120 automatic	023284	 025240	230V	150W	12V	2	10,5 A	3,5 - 7 A	—	15 A	12 x 17 x 29 cm	3,2 kg	TCB 120 automatic			30 > 120 Ah			OK	—	OK
START UP 80 automatic	024922	 025127	230V	350W	12V	2	13,5-25 A	9 - 17 A	50 A	—	12 x 18 x 32 cm	4,4 kg	START UP 80 automatic			45 > 170 Ah			OK	OK	OK


CHARGERS HF • INVERTER



p. 35

0,75 A 6/12V
GYS TECH 750

Ref. 024977



GO > 7,5V (12V)
> 3,75V (6V)



3,8 A 12V
GYS TECH 3800

Ref. 024939



COLD CHARGE
< 0°C > 0°C
GO > 7,5V



OPTION Ref 053137 :
Kit allume cigare /
Cigarette lighter adapter /
Adapterkit für Zigarettenanzünder

3,5/7 A 12/24V
GYS TECH 7000

Ref. 024953



COLD CHARGE
< 0°C > 0°C
GO > 16V (24V)
> 4,5V (12V)




PRODUCT LINE

				CHARGE			Recover	Fuse		
					Efficace / RMS	Moyen / Average (EN 60335)				
GYS TECH 750	024977	230V	16,5W	6 / 12V	0,75 A	0,75 A	—	—	12 x 16 x 24 cm	0,3 kg
GYS TECH 3800	024939	230V	60W	12V	0,8 - 3,8 A	0,8 - 3,8 A	—	10 A	10 x 27,5 x 26 cm	0,7 kg
GYS TECH 7000	024953	230V	160W	12V	7 A	7 A	•	10 A	10 x 31 x 29 cm	1,3 kg
				24V	3,5 A	3,5 A				

Recommendation										IP
GYS TECH 750	6V 12V									IP 60
GYS TECH 3800	12V									IP 65
GYS TECH 7000	12V 24V									IP 65



p. 35




BEST QUALITY !

3,8 A 12V
GYSFLASH 4A

Ref. 029156

NEW
03/2014




OPTION Ref 053519 :
Kit allume cigare /
Cigarette lighter adapter /
Adapterkit für Zigarettenanzünder

7 A 12V
GYSFLASH 7A

Ref. 029187



GYSflash 4A & 7A : included



		50 / 60 Hz			Start mini	Moyen / Average (EN 60335)	Equalize/Absorption	Floating				
GYSFLASH 4A	029156	170 > 260V	90W	12V	1V	0,8 - 3,8 A	14,6V (T > 0°)	15V (T < 0°)	13,6V	36 x 18,5 x 7 cm	0,9 kg	
GYSFLASH 7A	029187	170 > 260V	160W	12V	1V	0,8 - 7 A	14,6V (T > 0°)	15V (T < 0°)	13,6V	38,5 x 20,5 x 7 cm	1,1 kg	

Recommendation												
GYSFLASH 4A	12V										IP 65	Automatic
GYSFLASH 7A	12V										IP 65	Automatic

CHARGERS HF • INVERTER



2/12A 12V
GYSTECH 12/12

Ref. 024984

GO > 5V



CHARGERS TRADITIONAL



9A 12/24V
CT 160

Ref. 024106

Ref. 025325



12A 12/24V
CT 210

Ref. 024113

Ref. 025349



CHARGERS HF • INVERTER ON BOARD



GO > 1V

Résine/Resin/Harz/Resina

VIBRATIONS / VIBRATIONEN / VIBRATIONES
PROTECTED



**ULTRA
SHOCK RESISTANT**

5A 12V
INVERTER 5HF

Ref. 029170

**IP 67
ALUMINIUM
CASE**

RENAULT
1096600



Fuse X10 (for accessories)
10A : Ref.054530

 Recommendation										IP	
GYSTECH 12/12		12 V : Charge 2 > 200 Ah (Maintenance 2 > 250 Ah)								IP 20	•
INVERTER 5HF		On board/Embarqué 20 > 100 Ah (Maintenance 20 > 160 Ah)									—

		50 / 60 Hz			Start mini	Moyen / Average (EN 60335)	Equalize/Absorption	Floating		
GYSTECH 12/12	024984	230V	200W	12V	5V	2 A-12 A	—	—	22 x 26,5 x 8 cm	1,2 kg
INVERTER 5HF	029170	230V	80W	12V	1V	5 A	14,8V (liquid)	13,8V	20,5 x 12,5 x 7 cm	0,9 kg


Fuse X10
15A : Ref.054493 (CT 160)
20A : Ref.054509 (CT 210)



Recommendation							
CT 160	12V 24V	(12V) 25 > 160 Ah (24V) 15 > 90 Ah					
CT 210	12V 24V	(12V) 35 > 210 Ah (24V) 20 > 100 Ah					

				CHARGE						
				Reg	Efficace / RMS	Moyen / Average (EN 60335)		Fuse		
						Reg 1	Reg 2			
CT 160	024106	025325	230V, 50 / 60 Hz	190W	12/24V	12V > 2	13,5 A	7 A	15 A	20,5 x 30 x 13,5 cm
CT 210	024113	025349	230V, 50 / 60 Hz	260W	12/24V	12V > 2	7,5 A	3 A	20 A	22,5 x 33,5 x 14,5 cm
						12V > 2	18 A	8 A		
						24V > 2	9 A	4 A		

CHARGERS
AUTOMATIC
& MANUAL



Protection for on-board electronics



12A
CA 170

Ref. 024397



15A
CA 225

Ref. 024441



25A
CA 350

Ref. 024489














Fuse X10

15A : Ref.054493 (WATTMATIC 100)
20A : Ref.054509 (WATTMATIC 150)
25A : Ref.054516 (CA 170, CA 350, WATTMATIC 180)
30A : Ref.054523 (CA 225)



CHARGE



7 A	6/12V
BATIUM 7/12	
Ref. 024496	Ref. 024557



7 A	6/12/24V
BATIUM 7/24	
Ref. 024502	Ref. 024625



25 A	6/12/24V
BATIUM 25/24	
Ref. 024533	Ref. 024618



I REGULATED
IUoU
FAST CHARGE

IUlo

Specific charge
Traction batteries

2 in 1

SULPHATED
BATTERIES
SOS RECOVERY




SMART CHARGERS AUTOMATIC

15 A	6/12V
BATIUM 15/12	
Ref. 024519	Ref. 024632


SULPHATED
BATTERIES
SOS RECOVERY

15 A	6/12/24V
BATIUM 15/24	
Ref. 024526	Ref. 024588

SULPHATED
BATTERIES
SOS RECOVERY



MICRO-PROCESSOR CONTROL




V
AUTO DETECT



Fuse X10

15A : Ref.054493
(BATIUM 7/12 & 7/24)


30A : Ref.054523
(BATIUM 15/12 & 15/24)



				CHARGE 									
		50 / 60 Hz				Efficace / RMS	Moyen / Average (EN 60335)			Fuse			
							Reg 1	Reg 2	Reg 3				
BATIUM 7/12	024496  024557	230V	105W	6/12V	2	11 A	3 A	7 A	—	15 A	21 x 34 x 13 cm	4,8 kg	—
BATIUM 7/24	024502  024625	230V	210W	6/12/24V	2	11 A	3 A	7 A	—	15 A	21 x 34 x 13 cm	5,7 kg	—
BATIUM 15/12	024519  024632	230V	225W	6/12V	3	22 A	7 A	10 A	15 A	30 A	21 x 36 x 14 cm	5,9 kg	•
BATIUM 15/24	024526  024588	230V	450W	6/12/24V	3	22 A	7 A	10 A	15 A	30 A	21 x 36 14 cm	8,5 kg	•
BATIUM 25/24	024533  024618	230V	1150W	6/12/24V	3	37 A	7 A	15 A	25 A	—	28 x 42 x 23 cm	13,4 kg	•

Recommendation													
BATIUM 7/12	6V 12V	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 7/24	6V 12V 24V	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 15/12	6V 12V	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 15/24	6V 12V 24V	—	—	—	—	—	—	—	—	—	—	—	—
BATIUM 25/24	6V 12V 24V	35 > 180 Ah	—	—	—	—	—	—	—	—	—	—	—

TRADITIONAL
STARTERS
& CHARGERS



430 A 12/24V
PROSTART 430
Ref. 025219 Ref. 025226

610 A 12/24V
PROSTART 610
Ref. 025257 Ref. 025264

420 A 12/24V
NEOSTART 420
Ref. 025295 Ref. 025479

620 A 12/24V
NEOSTART 620
Ref. 025288 Ref. 025486



Fuses 200 A x 2
Ref. 054547



Fuses 200 A x 2
Ref. 054547

 Ref. 054547				 1		 CHARGE 					 START				 Recommendation			50 Ah > > > > 100 Ah > > > > 150 Ah > > > > 200 Ah	
PROSTART 430	025219	 025226	230 V	16 A	12 / 24 V	 3	Efficace / RMS 52 A	Moyen / Average (EN 60335) 35 A	Automatic —	pos. Manual •	min > max 20 > 700 Ah	1 V/C 250 A	0 V/C 430 A	 —	31 x 36,5 x 65 cm	23 kg	PROSTART 430		        
PROSTART 610	025257	 025264	230 V	16 A	12 / 24 V	3	72 A	45 A	—	•	20 > 1000 Ah	400 A	610 A	—	31 x 36,5 x 65 cm	26,5 kg	PROSTART 610		
NEOSTART 420	025295	 025479	230 V	16 A	12 / 24 V	3	70 A	45 A	—	•	20 > 1000 Ah	300 A	420 A	—	47 x 32 x 27 cm	20,5 kg	NEOSTART 420		
NEOSTART 620	025288	 025486	230 V	16 A	12 / 24 V	3	90 A	60 A	—	•	20 > 1350 Ah	360 A	620 A	—	47 x 32 x 27 cm	24 kg	NEOSTART 620		

AUTOMATIC
STARTERS
& CHARGERS


W2
p. 35

&

CHARGE

ELECTRONIC
CONTROL

MANUAL



Protection for on-board electronics

OVER
PROTECTION
VOLTAGE
AUTOMATIC
CONTROL

235 A 12V
GYSTART 235

Ref. 025318

600 A 12V
GYSTART 612 E

Ref. 025332



5m

700 A 12/24V
GYSTART 724 E

Ref. 025356



5m

900 A 12/24V
GYSTART 924.230

Ref. 025363




5m

1 200 A 12/24V
GYSTART 1224 T

Ref. 025394



5m



TRI
400V
3 ph



Fuses 200A x 2
Ref. 054547

					CHARGE 					START 						Recommendation 			50 Ah > > > > 100 Ah > > > > 150 Ah > > > > 200 Ah									
		50/60 Hz	I			Efficace / RMS	Moyen / Average (EN 60335)	Automatic	pos. Manual		1 V/C	0 V/C							       									
GYSTART 235	025318	230V	16 A	12V	2	25 A	17 A	•	•	20 > 400 Ah	140 A	235 A	—	24 x 18 x 35 cm	10,1 kg	GYSTART 235												
GYSTART 612 E	025332	230V	16 A	12V	ELECTRONIC 10  45	70 A	45 A	•	•	20 > 1000 Ah	350 A	600 A	•	31 x 36,5 x 65 cm	25,5 kg	GYSTART 612 E												
GYSTART 724 E	025356	230V	16 A	12/24V	ELECTRONIC 10  45	70 A	45 A	•	•	20 > 1000 Ah	400 A	700 A	•	31 x 36,5 x 65 cm	28,5 kg	GYSTART 724 E		 										
GYSTART 924.230	025363	230V	 16 A - 25 A	12/24V	ELECTRONIC 10  50	75 A	50 A	•	•	30 > 1100 Ah	650 A	900 A	•	36 x 28 x 78 cm	34 kg	GYSTART 924.230		 										
GYSTART 1224 T	025394	400V (TRI)	16 A	12/24V	3	80 A	60 A	•	•	65 > 1350 Ah	780 A	1200 A	•	42,5 x 34,5 x 71 cm	54,5 kg	GYSTART 1224 T		 										

TESTERS

TRADITIONAL



TBP 100
Ref 055131



TBP 500
Ref 055148

12V

ELECTRONIC

6V - 12V



BT 111 DHC
Ref 055155




BT 222 DHC
Ref 055216



BT 280 DHC
Ref 055261



RT 002 DHC
Ref 055230



GESTION LOGICIELLE
DE LA BATTERIE
BATTERY MANAGEMENT
SOFTWARE
SOFTWARE BATTERIE
MANAGEMENT



RT 777 DHC
Ref 055247

7
LANGUAGES
SPRACHEN

BT 501 DHC
Ref 055209



PRINTERS
DRUCKER

STANDARD
57mm (W)

BT 501 DHC
x2 (included)
Ref. 056220

RT 777 DHC
x1 (included)
Ref. 056237

				TEST			PRINT PAPER	DIGITAL	RESULT	TEMPERATURE COMPENSATION		
				BATTERY A	BATTERY V	CHARGING & STARTING SYSTEM VEHICLE						
TBP 100 <i>traditional</i>	055131	6-12 V	20>100 Ah	•	•	12V	—	—	5/10s	15 min	16x1,8x30	1,5
TBP 500 <i>traditional</i>	055148	12 V	10>160 Ah	•	•	12V	—	—	15s	15 min	27x26x13	8
BT 111 DHC <i>electronic</i>	055155	12 V	20>150 Ah	•	min 7 V	—	—	•	1s	instant	7x1,5x12	0,25
BT 222 DHC <i>electronic</i>	055216	12 V	20>150 Ah	•	min 7 V	12V	—	—	1s	instant	7x1,5x12	0,25
BT 280 DHC <i>electronic</i>	055261	12 V	4>150 Ah	•	min 4,5 V	12V	—	rétro-éclairé /back-lit	1s	instant	12x7,9x227	0,25
RT 002 DHC <i>electronic</i>	055230	6-12 V	7>230 Ah	•	min 1,5 V	12V 24V	—	rétro-éclairé /back-lit	1s	instant	11,5x5x19	0,8
BT 501 DHC <i>electronic</i>	055209	6-12 V	7>230 Ah	•	min 1,5 V	12V 24V	•	•	1s	instant	11x4x19,5	0,4
RT 777 DHC <i>electronic</i>	055247	6-12 V	7>230 Ah	•	min 1,5 V	12V 24V	•	rétro-éclairé /back-lit	1s	instant	13x6,4x25,1	0,7

Recommendation	Test		PRINT PAPER					
	batteries/Battery/ Ladegeräte	Circuit alternateur/ Alternator Circuit/ Lichtmaschinen Schaltkreis						
TBP 100 <i>traditional</i>	6V 12V	12V	—		20 > 100 Ah			
TBP 500 <i>traditional</i>	12V	12V	—		10 > 160 Ah			
BT 111 DHC <i>electronic</i>	12V	—	—		20 > 150 Ah			
BT 222 DHC <i>electronic</i>	12V	12V	—		20 > 150 Ah			
BT 280 DHC <i>electronic</i>	12V	12V	—		4 > 150 Ah			
RT 002 DHC <i>electronic</i>	6V 12V	12V 24V	—		7 > 230 Ah			
BT 501 DHC <i>electronic</i>	6V 12V	12V 24V	•		7 > 230 Ah			
RT 777 DHC <i>electronic</i>	6V 12V	12V 24V	•		7 > 230 Ah			

BOOSTERS + POWER SUPPLY

WU

Floating Process
Charge 100%

p. 35

1 000 A 12V
GYSPACK ONE

Ref. 025073

1V/C 300 A



NEW
12/2013

1 250 A 12V
GYSPACK AUTO/ GYSPACK 400

1V/C 480 A

Ref. 026230

Ref. 025424

Ref. 025455



Power Supply
18 Ah · 12V DC



NEW
12/2013

1 250 A 12V
GYSPACK AIR

1V/C 480 A

Ref. 026322

Ref. 025431

Isolated clamps
500 A
1,1 m
ø 25 mm²



Power Supply
18 Ah · 12V DC



+ Compressor

Air Kit
included
4 bars




SELECTION P. 34

1 750 A 12V
GYSPACK PRO

Ref. 026155

WU

p. 35



Power Supply
22 Ah · 12V DC

AUTOMATIC CHARGER
Power in 12V



included

Isolated clamps
500 A
1,1 m
ø 25 mm²



2 500 A 12V
GYSPACK 750

1V/C 750 A

Ref. 026179

1 REGULATED IVOU FAST CHARGE

p. 35



Power Supply
26 Ah · 12V DC

AUTOMATIC CHARGER
Power in 12V



included

Isolated clamps
600 A
1,3 m
ø 25 mm²



3 200 A 12V
1 600 A 24V
GYSPACK TRUCK


1V/C 750 A

1V/C 650 A

Ref. 025448

1 REGULATED IVOU FAST CHARGE

p. 35



Power Supply
44 Ah · 12V DC

AUTOMATIC CHARGER
Power in 12V



included

Isolated clamps
600 A
1,8 m
ø 25 mm²



GYSPACK 750
GYSPACK TRUCK
AUTOMATIC CHARGER
Power in 230V/12V
included Ref. 054684

Fuses 200 A x2
GYSPACK 750
Ref. 054547
Fuses 300 A x2
GYSPACK TRUCK
Ref. 054561



Après chaque utilisation
After each use
Nach jeder Anwendung

		12V	START	ON/OFF	Power Supply	Charge 230V	TEST OK	Box	Weight
		Inside	1V/C Cranking CC Peak Battery			EXTERNAL 12V DC			
GYSPACK PRO	026155	22 Ah	12V 600 A 1100 A 1750 A	•	—	EXTERNAL 12V DC	•	24 x 17 x 285 cm	5,8 kg
GYSPACK 750	026179	26 Ah	12V 750 A 1450 A 2500 A	•	2 x 200 A	EXTERNAL 12V DC	•	33 x 14 x 35 cm	7 kg
GYSPACK TRUCK	025448	2 x 22 Ah	12V 750 A 1450 A 3200 A 24V 650 A 1300 A 1600 A	•	1 x 300 A	EXTERNAL 12V/2 A DC	•	35,5 x 19,5 x 43 cm	10 kg



Après chaque utilisation
After each use
Nach jeder Anwendung

		12V	START	ON/OFF	Power Supply	Charge 230V	TEST OK	Box	Weight
		Inside	1V/C Cranking CC Peak Battery			EXTERNAL 12V DC			
GYSPACK ONE	025073	12 Ah	300 A 600 A 1000 A	—	—	EXTERNAL 12V DC	•	24 x 17 x 285 cm	5,8 kg
GYSPACK AUTO/400	026230 025424	18 Ah	480 A 900 A 1250 A	—	—	EXTERNAL 12V DC	•	33 x 14 x 35 cm	7 kg
GYSPACK AIR	026322 025431	18 Ah	480 A 900 A 1250 A	•	4 bars	EXTERNAL 12V DC	•	35,5 x 19,5 x 43 cm	10 kg

GYSPACK AUTO
GYSPACK AIR
GYSPACK 400
GYSPACK PRO
AUTOMATIC CHARGER
Power in 230V/12V
included Ref. 054677
Ref. 054660



BOOSTERS
CAR + TRUCK



p. 35

SELECTION P. 34

1 800 A	12V	1V/C 640 A
GYSPACK 650		

Ref. 026254



3 100 A	12V	1V/C 830 A
GYSPACK 810		

Ref. 026278






3600 A	12V	1V/C 900 A
1 800 A	24V ★	1V/C 700 A
STARTPACK 12.24		

Ref. 026285

6200 A	12V	1V/C 1300 A
3100 A	24V ★★ ★	1V/C 1200 A
GYSPACK PRO 12.24		

Ref. 026452



Fuses 200 A x 2
Ref. 054547



		12V	START				TEST	CHARGER	Protection	Power out	Fuse	Fuse			
		Inside	1V/C	Cranking CC	Peak Battery		OK	INSIDE		Memory					
GYSPACK 650	026254	16 Ah	12V 640 A	1200 A	1800 A	•	3 A	•	•	→ 12V DC	15 A	200 A	2 x 1,4 m ø 25 mm ²	23 x 35 x 35 cm	13 kg
GYSPACK 810	026278	30 Ah	12V 830 A	1700 A	3100 A	•	3 A	•	•	→ 12V DC	15 A	2 x 200 A	2 x 1,8 m ø 35 mm ²	18 x 38 x 31 cm	16,6 kg
STARTPACK 12.24	026285	2x16 Ah	12V 900 A	1700 A	3600 A	•	7 A	•	•	—	20 A	2 x 200 A	2 x 1,8 m ø 35 mm ²	21 x 35 x 56 cm	23,5 kg
GYSPACK PRO 12.24	026452	2x30 Ah	12V 1300 A	2400 A	6200 A	•	7 A	•	•	—	20 A	2 x 200 A	2 x 2 m ø 50 mm ²	12 x 64 x 97 cm	45,5 kg
			24V 700 A	1350 A	1800 A										
			24V 1200 A	2250 A	3100 A										

12V

Recommendation	
GYSPACK 650	
GYSPACK 810	

24V

Recommendation	
GYSPACK TRUCK	
STARTPACK 12.24	★
GYSPACK PRO 12.24	PRO ★★ ★


BOOSTER TRUCK & BUS

CHARGER AUTOMATIC X2



12/24V
ENERGY STATION



Ref. 026148



Batteries non fournies
Batteries not provided
Ohne Batterie



Après chaque utilisation
After each use
Nach jeder Anwendung




MEMORY AUTO SAVE

SAUVEGARDE MÉMOIRE OBD / Memory auto save
/ Speicherschutz / Salvaguardia memorias
/ Salvaguardas de memória / Αυτόματη αποθήκευση ρυθμίσεων
/ Сохранение настроек/ 记忆储存器

GYSPACK OBD

Ref. 054998

Ref. 055001



Après chaque utilisation
After each use
Nach jeder Anwendung

INSIDE	MEMORY SAVER			
12V 7 Ah	OBD < 4 A	Battery < 4 A	25 x 18 x 25 cm	3 kg



< 4A

ENERGY STATION

12V 24V

ENERGY STATION

026148

START
selon batteries
/according to battery

CHARGE

12V	24V	min > max	Moyen / Average (EN 60335)	Efficace / RMS
•	•	35 > 225 Ah	2 x 15 A	2 x 22 A



Fuse



70 x 62 x 92 cm



36 kg + batteries




2 x 2,5 m - ø 35 mm²

SAUVEGARDE MÉMOIRE / Memory auto save / Speicherschutz

230V/12V

Ref. 055018



JUMPER CABLES
CONSUMER



Ref.			
056367	200 A (car 1,2 l)	2,5 m	7 mm ²

ISOLATED CLAMPS



Ref.			
056398	200 A (car 1,5 l)	2,8 m	10 mm ²
056411	320 A (car 2,5 l)	3 m	16 mm ²
056428	500 A (car 3/5,5 l)	3,5 m	25 mm ²
056442	700 A (truck 4/7 l)	4,5 m	35 mm ²

ISOLATED CLAMPS & LED



Ref.			
056374	300 A (car 2,5 l)	3 m	16 mm ²
056381	500 A (car 4,5/5,5 l)	3,5 m	25 mm ²

JUMPER CABLES
PROFESSIONAL

ISOLATED CLAMPS

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN - Pinzas aisladas - Garras aisladas
• Geïsoleerde klemmen • Μονωμένοι ακροδέκτες • Изолированные зажимы • 绝缘充电夹



Ref.			
056312	200 A (car 1,5 l)	2,8 m	10 mm ²
056329	320 A (car 2,5 l)	3 m	16 mm ²
056336	500 A (car 3/5,5 l)	3,5 m	25 mm ²
056343	700 A (truck 4/7 (PRO))	4,5 m	35 mm ²

MADE IN P.R.C

PRO

PINCES LAITON, NON ISOLÉES - Brass clamps, NOT INSULATED - Messingklemmen, nicht isoliert - pinzas de latón, no aisladas
• Koperen klemmen, niet geïsoleerd • Garras bronce, latão isoladas • Ακροδέκτες χαλκού χωρίς μόνωση • ЛАТУННЫЕ ЗАЖИМЫ, НЕИЗОЛИРОВАННЫЕ
• 黄铜夹, 无绝缘



Ref.			
056206	320 A	3 m	16 mm ²
564015	500 A	3 m	25 mm ²
056404	700 A	4,5 m	35 mm ²
056602	1000 A	5,1 m	50 mm ²


MADE IN P.R.C

BRASS CLAMPS



MADE IN FRANCE

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN - Pinzas aisladas - Garras aisladas
• Geïsoleerde klemmen • Μονωμένοι ακροδέκτες • Изолированные зажимы • 绝缘充电夹



Ref.			
056541	700 A	4,5 m	35 mm ²

SUPER PRO



MADE IN FRANCE



Ref.			
056619	1000 A	5 m	50 mm ²


POWER INVERTER 12V > 230V



CONVERGYS 150
Ref. 027015



CONVERGYS 300
Ref. 027053



PSW 8300
Ref. 027114



PSW 8600
Ref. 027169



Conversion Chart / Table:

horse power to watts	watts to horse power
hp = W	W = hp
0,1 = 73,5	100 = 0,1360
0,2 = 147,1	200 = 0,2719
0,3 = 220,6	300 = 0,4079
0,4 = 294,2	400 = 0,5438
0,5 = 367,7	500 = 0,6798
1 = 735,5	1000 = 1,3596
2 = 1471,0	2000 = 2,7192
3 = 2206,5	3000 = 4,0789
4 = 2942,0	4000 = 5,4385



PSW 81500
Ref. 027220




	Power	Peak power	Pure Sin Wave	Optimum Efficiency	Input DC	Output AC	Output USB DC	max 150W	Universal			
CONVERGYS 150	027015	027008	150W	300W	—	90,5 %	12V	230V	5V - 500 mA	•	—	•
CONVERGYS 300	027053	027046	300W	600W	—	85 %	12V	230V	5V - 500 mA	•	•	•
PSW 8300	027114	027107	300W	600W	•	85 %	12V	230V	5V - 500 mA	—	•	•
PSW 8600	027169	027152	600W	1200W	•	85 %	12V	230V	5V - 500 mA	—	•	•
PSW 81500	027220	027190	1500W	3000W	•	85 %	12V	230V	5V - 500 mA	—	•	•



CONVERGYS 150	150W
CONVERGYS 300	300W
PSW 8300	300W
PSW 8600	600W
PSW 81500	1500W

DHC 54E STATION MULTICHARGE POUR BATTERIES - Multi charge station for batteries - multi-ladestation für starter-batterien

Charge automatique • Automatic charge • Automatischer Ladevorgang
4 x 5A 12V (liquid/gel)
5 étapes • 5 steps • 5 Schritte
Pulse/Boost/Egalisation/100%/Floating
Maintenance/Zusatzhilfskit



Multicharge Station DHC 54E
Ref. 025097



KIT SOLAIRE DE MAINTIEN DE CHARGE - Solar powered charger - Solarpanel zur Ladeerhaltung - Kit solar de mantenimiento de carga - Солнечная панель для поддержания заряда в наборе с аксессуарами



PINCES - Clamps • Klemmen • Pinzas • Garras • Ακροδέκτες • Зажимы • 充电夹

40 A	200 A	300 A	600 A	850 A
• (x2) Ref.053106	• Ref.053502 • Ref.053403	• Ref.053700 • Ref.053601	• Ref.053779 • Ref.053786	• Ref.053816 • Ref.053793

COSSES BATTERIE - Battery Terminal - Polklemmen - Terminales batería - Accupool - Terminais de bateria - Πόλος μπαταρίας - Контакты аккумуляторной - батареи - 电池端子

ø 10 mm / 35 mm ²	ø 13 mm / 50 mm ²	ø 16 mm / 70 mm ²
x1 054400	x25 Ref.054431	x25 Ref.054417
x25 Ref.054448	x25 Ref.054332	x25 Ref.054424
	x25 Ref.054349	x25 Ref.054363
		x25 Ref.054370
		x25 Ref.054387

FUSIBLES - Fuses - Sicherungen - Fusibles - Zekeringen - Fusíveis - Ασφάλειες - Плавкие предохранители - 保險絲

Quick Connector ø 10 mm / 50 mm ² I max = 1000 A Ref. 054455
x10
for Gystart & Prostart (before July 2007) 100A : 054486
x10
for Gystart & Prostart (after July 2007) 200A : 054547 300A : 054561
x2

AUTRES - Others - Andere - Otros - Outros - Άλλα - Разное - Другое par Разное - 其他

Protection anti-arc 12V • Anti-arc protection 12V • Lichtbogenschutz 12V
• Protección anti-arco 12V • Piekspanningsbeveiliging 12V
• Protecção anti-faísca 12V
• Αντι-σπινθηρική προστασία 12V
• Защита против дуги 12В
• 12V 抗电弧保护



Pèse acide antigel • Acidimeter (PH Meter)
• Säure/Frostschutzmittel-Tester • Acido densímetro anticongelante
• Zuurweger • Medidor de PH (ácido)
• Μετρητής οξύτητας (PH) • Ацидиметр (pH-метр) • 防冻酸度计



CHOOSE YOUR BOOSTER

CHOISISSEZ VOTRE BOOSTER

	12 V							12 - 24 V			
	GYSPACK ONE	GYSPACK AUTO	GYSPACK AIR	GYSPACK PRO	GYSPACK 650	GYSPACK 750	GYSPACK 810	GYSPACK TRUCK	STARTPACK 12.24	GYSPACK PRO 12.24	ENERGY STATION
	025073	026230 025455	026322	026155	026254	026179	026278	025448	026285	026452	026148
	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V
	24V							24V	24V	24V	24V
1V/C	300 A	480 A	480 A	600 A	640 A	750 A	830 A	750 (12V)	900 A (12V)	1300 A (12V)	
								650 (24V)	700 A (24V)	1200 A (24V)	
CC	600 A	900 A	900 A	1100 A	1200 A	1450 A	1700 A	1450 A (12V)	1700 A (12V)	2400 A (12V)	
								1300 A (24V)	1350 A (24V)	2250 A (24V)	
PEAK	1000 A	1250 A	1250 A	1750 A	1800 A	2500 A	3100 A	3200 A (12V)	3600 A (12V)	6200 A (12V)	
								1600 A (24V)	1800 A (24V)	3100 A (24V)	
12V	12 Ah	18 Ah	18 Ah	22 Ah	16 Ah	26 Ah	30 Ah	2 x 22 Ah	2 x 16 Ah	2 x 30 Ah	
OK	—	—	•	•	•	•	•	•	•	•	—
TEST	—	•	•	•	•	•	•	—	—	—	•
Hand icon	outside 0,5 A	outside 0,5 A	outside 0,5 A	outside 0,5 A	inside 2,5 A	outside 2 A	inside 2,5 A	outside 2 A	inside 7 A	inside 7 A	inside 2 x 15 A
TV icon		12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	—	—	—
Welder icon	—	—	•	—	—	—	—	—	—	—	—
Sun icon	—	—	•	•	—	•	—	•	—	—	—
Dimensions	0,5 m ø16 mm²	0,5 m ø16 mm²	1,1 m ø25 mm²	1,1 m ø25 mm²	1,4 m ø25 mm²	1,3 m ø25 mm²	1,8 m ø35 mm²	1,8 m ø25 mm²	1,8 m ø35 mm²	1,8 m ø35 mm²	2,5 m ø50 mm²
Area	22 x 24 x 15	33 x 14 x 35	34 x 20 x 43	34 x 20 x 43	33 x 20 x 33	33 x 16 x 38	33 x 20 x 33	35 x 19 x 44	17 x 33 x 48	57 x 34 x 94	70 x 62 x 92
Weight	6 kg	7 kg	8,9 kg	7,9 kg	11 kg	13 kg	15 kg	18 kg	23 kg	31 / 40 kg	36 kg +

★

★★★

★★★★★

MINI PRO

PRO

UNIVERSAL PRO



ATTENTION HORS UTILISATION
Laisser le chargeur branché
en permanence.

CAUTION ON STAND BY
Keep your GYSPACK connected to the mains supply.

ACHTUNG AUSSER BETRIEB
Lader dauernd angeschlossen lassen.


ATTENTION CUANDO ESTA APAGADO
Dejar el cargador conectado permanentemente.

OPGELET BIJTEN GEBRUIK
Laat de lader onafgebroken aangesloten.

BATTERIES DE DÉMARRAGE - Automotive batteries - Starterbatterien - Baterías de arranque - Automotive accu's
- Baterías de Automóvil - Μπαταρίες οχημάτων - Пусковые батареи - 汽车启动电池

TRADITIONAL

W




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



AUTOMATIC

W2




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



WU




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



WUoU




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



AUTOMATIC FAST CHARGE

IWUoU




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



I.I.I




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



I




Recommendation

LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



I REGULATED I UoU FAST CHARGE



Recommendation


LIQUID	LIQUID Calcium	Silver AGM	START/STOP (A)	GEL Sealed	OPTIMA maXXima
★	★	★	★	★	★
UNIVERSAL	MAINTENANCE	EASY USE	HIGH TECH		



BATTERIES DE TRACTION - Traction batteries - Traktionsbatterien - Baterías de tracción - Tractieaccu's - Baterías de Tracción
- Μπαταρίες έλξεως - Тяговые батареи - 牵引用铅酸蓄电池


AUTOMATIC FAST CHARGE

I UoU




Recommendation

Traction batteries ★★★★★
High Technologie ★



24V 150Ah
(GYS Recommendation : BATIUM 15/24 - 25/24)

12V 80Ah + 12V 60Ah + 12V 120Ah + 12V 100Ah = 12V 360Ah
(GYS Recommendation : Inverter 40HF - 70 HF)



24V 290Ah
(GYS Recommendation : CA 350 - BATIUM 25/24 - INVERTER 70.24 HF)

Conversion Chart / Table:

horse power to watts	watts to horse power
hp = W	W = hp
0,1 = 73,5	100 = 0,1360
0,2 = 147,1	200 = 0,2719
0,3 = 220,6	300 = 0,4079
0,4 = 294,2	400 = 0,5438
0,5 = 367,7	500 = 0,6798
1 = 735,5	1000 = 1,3596
2 = 1471,0	2000 = 2,7192
3 = 2206,5	3000 = 4,0789
4 = 2942,0	4000 = 5,4385



GYS France

BP 4159
53941 Saint-Berthevin
Laval cedex France
Fax : +33 (0)2 43 68 35 21

www.gys.fr
E-mail : contact@gys.fr

GYS Germany

Professor-Wieler-Straße 11
52070 Aachen - Deutschland
Tel : +49 (0) 241 / 189-23-710
Fax : +49 (0) 241 / 189-23-719
www.gys-schweissen.com
E-mail : aachen@gys.fr

GYS UK

Unit 2
Spartan Close
Tachbrook Park
Warwick - United Kingdom - CV34 6RS
Tel : +44 (0) 1926 338 609
Fax : +44 (0) 1926 429 764
www.gys-welding.com
E-mail : uk@gys.fr

GYS India

20, Huzur Road - Near Anna Statue
Coimbatore - 641018
Tamil Nadu - India
Tel : +91. 88708. 71111
E-mail : r.samal@gys.fr

GYS China

Lot N°15
6666 bd Songze
201706 Qingpu Shanghai - China
Tel : +86 (21) 6221 4461
Fax : +86 (21) 5226 0067
www.gysasia.com
E-mail : contact@gys-china.com.cn

Bao Zhi Long Electrical Equipment (JV GYS)

Room: 203C
Building: N°1
N°518 Shen Wang Road
Minhang District Shanghai - China
Tel1 : +86 (21) 52217650
Tel2 : +86 (21) 52217651
Tel3 : +86 (21) 52217652
Fax : +86 (21) 52217653
www.bzl-china.com
E-mail : mz@bzl-china.com

International Events



Distributed by :

